CHL
MATERIALS HANDLING

PRODUCTS RANGE

General Description
of the Company

Anhui Forklift Group Co., Ltd. (Hereinafter as AFG), as a state-owned company, was originally founded in 1958. During the past 55 years' development, AFG always focus on forklift business. We have been No.1 in China since 1991, and ranked No.8 in the world in 2008. Our core holding company-- Anhui Heli Co., Ltd. is the only Chinese forklift company listed in stock market.

CHL is one forklift brand of AFG, mainly to supply reliable and affordable lift trucks. Based on the AFG's advanced technology and equipment, CHL trucks' quality is at TOP level in China. Mass production helps to lower cost, SAP system and Lean production ensure high productivity. Those promise CHL trucks always be reliable and competitive.

ANHUI HELI CO., LTD.
ADD: NO.668 Fangxing Street,Economical Development Zone,Hefei,P.R.China
TEL : (86 551)63639458
WEBSITE : www.chlforklift.com
Email: chl@chlforklift.com

Catalog No.190927 Fokeli Print

5 Warehouse truck

Pallet truck

>> CBD15-170
- Capacity 1500kg
- Fork length 1150/1200mm
- Fork width 160mm
- 24V/75Ah/85Ah
- DC Controller
- Option:
  Fork lowered height 75mm

>> CBD15/20J-Li、CBD15-DLi
- Capacity 1500/2000kg、1500kg
- Fork length 1150mm
- Fork width 150mm
- 24V/35Ah(15J)、48V/20Ah(20J)
  24V/52(20)Ah (DLi)
- DC Controller
- Lithium battery

LiION

>> CBD15-610
- Capacity 1500kg
- Fork length 1150/1200mm
- Fork width 160mm
- 24V/85Ah
- DC Controller
- Option:
  Fork lowered height 75mm

>> CBD18/20-180
- Capacity 1800/2000kg
- Fork length 1150/1200mm
- Fork width 170mm
- 24V/210Ah
- AC Controller

>> CBD20J
- Capacity 2000kg
- Fork length 1150mm
- Fork width 160mm
- 24V/100Ah
- DC Controller

>> CBD20-150
- Capacity 2000kg
- Fork length 1150/1200mm
- Fork width 170mm
- 24V/210Ah
- AC Controller
- Option:
  Fork lowered height 75mm

>> CBD20-410
- Capacity 2000kg
- Fork length 1150/1200mm
- Fork width 170mm
- 24V/210Ah
- AC Controller
- Rider

>> CBD20/25/28/30-460/470
- Capacity 2000/2500/2800/3000kg
- Fork length 1150/1200mm
- Fork width 170mm
- 24V/270Ah/280Ah
- AC Controller
- Rider

>> CBD20-490
- Capacity 2000kg
- Fork length 1150/1200mm
- Fork width 170mm
- 24V/280Ah
- AC Controller
- Rider

>> CBD35-510/520/530
- Capacity 3500kg
- Fork length 2432mm
  /1212-1517mm
- Fork width 250mm/230mm
- 24V/360Ah
- AC Controller
- Rider
- Option: walkie

Stacker

①Fork over

>> CBS10/15/20J
- Capacity 1000kg
- lift height 1600mm(single stage)、
  2000-3500mm
- 12V/120Ah
- DC Controller
- Semi-electric

>> CDD12-060
- Capacity 1200kg
- lift height 2000-3600mm
- 24V/210Ah
- DC Controller

>> CDD10-070
- Capacity 1000kg
- lift height 2000-3300mm
- 24V/85Ah
- DC Controller

>> CDD10-080
- Capacity 1000kg
- lift height 1600/1950mm
- 24V/85Ah
- DC Controller

>> CDD12J (D)
CDD15J
- Capacity 1200/1500kg
- lift height 1600mm(Mono mast)、
  2000-3500mm
- 24V/100Ah
- DC Controller

>> CDD12/14
- Capacity 1200/1400kg
- lift height 1400-4000mm
- 24V/210Ah/280Ah
- AC Controller

>> CDD16/20
- Capacity 1600/2000kg
- lift height 1400-5000mm
- 24V/280Ah
- AC Controller

>> CDD16/20J
- Capacity 1600/2000kg
- lift height 1600mm(single stage)、
  2000-3500mm
- 24V/100Ah/210Ah
- AC Controller

②Straddle

>> CBS10/12J-K
- Capacity 1000/1200kg
- lift height 1600mm(single stage)、
  2000-3500mm
- 12V/120Ah
- DC Controller
- Semi-electric

>> CTD10-050
- Capacity 1000kg
- lift height 2000-3300mm
- 24V/85Ah
- DC Controller

>> CTD10-090
- Capacity 1000kg
- lift height 1600/1950mm
- 24V/85Ah
- DC Controller

>> CDD12J-K
- Capacity 1200kg
- lift height 1600mm(single stage)、
  2000-3500mm
- 24V/100Ah
- DC Controller

>> CTD14/16/20
- Capacity 1400/1600/2000kg
- lift height 1400-4000mm
- 24V/280Ah
- AC Controller
- Standard 2-stage

>> CTD16/20
- Capacity 1600/2000kg
- lift height 3700-5800mm
- 24V/280Ah
- AC Controller
- Full free 3-stage

>> CTD16-960H
- Capacity 1600kg
- lift height 3700-5000mm
- 24V/270Ah
- AC Controller

>> CDD16/20J-K
- Capacity 1600/2000kg
- lift height 1600mm(single stage)、
  2000-3500mm
- 24V/100Ah/210Ah
- AC Controller

③Counterbalanced

>> CPD06-970
- Capacity 600kg
- Standard 2-stage
- lift height 1400-3300mm
- 24V/270Ah
- AC Controller

>> CPD12-970/910
- Capacity 1200kg
- Standard 2-stage
- lift height 1400-3600mm
  /2500-3300mm
- 24V/270Ah
- AC Controller

>> CPD16-(D)970
- Capacity 1600kg
- Standard 2-stage
- lift height 1400-4000mm
  /3700-4500mm
- 24V/270Ah
- AC Controller

④ New products

>> CBD20J-B
- Capacity 2000kg
- Fork length 1150mm
- Fork width 150mm
- 24V/32Ah
- DC Controller
- Semi-electric
- Pallet truck

>> CBD15/18/20J-Li2
- Capacity 1500/1800/2000kg
- Fork length 1150mm
- Fork width 150mm
- 24V/28Ah (15/18J)
- 48V/20Ah (20J)
- DC Controller
- Lithium battery
- Pallet truck

LiION

>> CDD15J-ZSM
- Capacity 1500kg
- lift height 4000/4600mm (3-stage STD)
- 24V/210Ah
- AC Controller
- Fork over Stracker

>> CDD12/15-070E
- Capacity 1200/1500kg
- lift height 2000-3300mm
- 24V/85(105)Ah
- DC Controller
- Fork over Stracker

1 Forklift truck

Internal combustion

>> 1-1.8t CPC(D)10-18

- Capacity 1000-1800kg
- Lifting height 3000mm
- Max.lifting height 7000mm
- Load center 500mm
- Diesel

>>2-3.5t CPC(D)20-35

- Capacity 2000-3500kg
- Lifting height 3000mm
- Max.lifting height 6000mm
- Load center 500mm
- Diesel

>> K2C series 2-3.5t CPC(D)20-35

- Capacity 2000-3500kg
- Lifting height 3000mm
- Max.lifting height 7500mm
- Load center 500mm
- Diesel

>> 4-5t CPC(D)40-50

- Capacity 4000-5000kg
- Lifting height 3000mm
- Max.lifting height 6000mm
- Load center 500mm
- Diesel

>> 5-7.5t CPCD50-75

- Capacity 5000-7500kg
- Lifting height 3000mm
- Max.lifting height 7000mm
- Load center 600mm
- Diesel

>> 8-10t CPCD80-100

- Capacity 8000-10000kg
- Lifting height 3000mm
- Max.lifting height 7000mm
- Load center 600mm
- Diesel

>> 2-3.5t CPQ(Y)D20-35

- Capacity 2000-3500kg
- Lifting height 3000mm
- Max.lifting height 7000mm
- Load center 500mm
- LPG/Gasoline

>> K2C series 2-3.5t CPC(D)20-35

- Capacity 2000-3500kg
- Lifting height 3000mm
- Max.lifting height 7500mm
- Load center 500mm
- LPG/Gasoline

>> 4-5t CPQ(Y)D40-50

- Capacity 4000-5000kg
- Lifting height 3000mm
- Max.lifting height 6000mm
- Load center 500mm
- LPG/Gasoline

Electric

①Four-wheel

>> 1-1.8t CPD10-18

- Capacity 1000-1800kg
- Lifting height 3000mm
- Max.lifting heighe 7000mm
- Load center 500mm
- 48V/400Ah/480Ah

>> 2-2.5t CPD20-25

- Capacity 2000-2500kg
- Lifting height 3000mm
- Max.lifting heighe 7000mm
- Load center 500mm
- 48V/600Ah

>> 3-3.5t CPD30-35

- Capacity 3000-3500kg
- Lifting height 3000mm
- Max.lifting heighe 7000mm
- Load center 500mm
- 80V/480Ah/560Ah

>> 4-5t CPD40-50

- Capacity 4000-5000kg
- Lifting height 3000mm
- Max.lifting heighe 6000mm
- Load center 500mm
- 80V/600Ah/650Ah

②Three wheel

>> 1.5-2T CPD15/20SQ

- Capacity 2000-2500kg
- Lifting height 3000mm
- Max.lifting heighe 7000mm
- Load center 500mm
- 48V/600Ah

2 Heavy Vehicle

Big Truck

>> CPCD120

- Capacity12000kg
- Load center 600mm
- Max lifting height 6500mm
- Lift height 3000mm
- Diesel

>> CPCD140-180

- Capacity14000-18000kg
- Load center 600mm
- Max lifting height 6500mm
- Lift height 3000mm
- Diesel

>> CPCD200-250

- Capacity20000-25000kg
- Load center 1200mm
- Max lifting height 8000mm
- Lift height 4000mm
- Diesel

>> CPCD280-320

- Capacity28000-32000kg
- Load center 1200mm
- Max lifting height 8000mm
- Lift height 4000mm
- Diesel

>> CPCD420-460

- Capacity42000-46000kg
- Load center 1200mm
- Max lifting height 8000mm
- Lift height 4000mm
- Diesel

>> RSH4527/31

- Capacity (first/second/third) 45000/(27000/31000) /(13000/15000)kg
- Max lifting height(first row) 15050mm
- Diesel
- Reach stacker

3 Tow tractor

Internal combustion

>> QYCD20-30

- Max drawbar pull 2000-3000N
- Max travel speed 24-30km/h
- Diesel/Gasoline

>> QYCD30-35

- Max drawbar pull 3000-3500N
- Max travel speed 26km/h
- Diesel

>> QYCD40-50

- Max drawbar pull 4000-5000N
- Max travel speed 23km/h
- Diesel

>> QYCD60-80

- Max drawbar pull 6000-8000N
- Max travel speed 30km/h
- Diesel

>> QYCD35-50

- Max drawbar pull 3500-5000N
- Max travel speed 24km/h
- Diesel

Electric

>> QYD20/30/45S

- Capacity 2000-4500kg
- Travel speed 7/6km/h
- 24V/210Ah/280Ah/430Ah

>> QYD15/20/30/40/50/60S

- Capacity 1500-6000kg
- Travel speed 9/10km/h
- 24V/280Ah/350Ah 48V/280Ah/350Ah /380Ah/420Ah

>> QYD20-70

- Capacity 2000-7000kg
- Travel speed 9/8 km/h
- 24V/240Ah/320Ah 48V/210Ah/240Ah/320A

>>BD10-50

- Capacity 1000-5000kg
- CURTIS Controller
- Option:Lithium battery

>>BD150-300

- Capacity 15000-30000kg
- CURTIS Controller

4 Reach truck

Stand-up

>> 1.5-1.8t CQD15-18

- Capacity 1500-1800kg
- Lifting height 3100mm
- Max.lifting heighe 6500mm
- Load center 500mm
- 48V/345Ah/360Ah

>> 1.2-1.5T CQDM12/15-810

- Capacity 1200-1500kg
- Standard 2-stage/Full free 3-stage
- Reach distance 425mm
- Lifting height 1400-4000mm /3700-4500mm
- 24v/280Ah

Sit-down

>> 1.6-2t CQD16-20

- Capacity 1600-2000kg
- Lifting height 4250/4600mm
- Max lifting height 8500-12500mm
- Load center 600mm
- 48V/500Ah

5 Others

Platform Trailer&attachments

>> TCP10~TCP800

- Capacity500-80000kg
- Hooking height 450mm(Adjustable)
- Platform Trailer

>> GC-series Sideshifters

>> Bale Clamps